

- Manufactured from high strength copper alloy with stainless steel screw.
- UL listed and CSA certified for direct burial in earth or concrete.
- Tested to UL 467.
- GBL-4DBT and GBL-4DBTH are UL2703 Listed.
- Lay-in feature for ease in installation.
- For copper conductor only.
- Rated for grounding and bonding.
- Green color, universal to identify ground aids in visual inspection.
- T Tin Plated
- H Stainless Steel Hex Head Screw
- Stainless mounting hardware kits available
- GBL-MH1 contains 1 each #10-32 x 3/4 bolt, nut, star washer, lock washer, flat washer
- GBL-MH2 contains 1 each #10 x 3/4 self-tapping screw, star washer, lock washer, flat washer (Not for PV application)
- GBL-MH3 contains 1 each 1/4-28 x 3/4 bolt, nut, star washer, lock washer, flat washer
- GBL-MH4 contains 1 each 1/4 x 3/4 self-tapping screw, star washer, lock washer, flat washer (Not for PV application)
- GBL-MHU contains 1 each #10-32 x 1/2 bolt, #10-32 x 3/4 bolt, nut, star washer, lock washer, flat washer
- UL File E34440, UL E3544

Item ID	Ground Conductor Range	Length	Width	Height	Bolt/Stud Size	Hex Size	Plating	Standard Package Quantity	NAED/UPC Number
GBL-4DBT	4-14 AWG	1.1500	0.3750	0.8250	#10	S	Tin	50	0783669960181