

# Enphase AC Battery

The Enphase AC Battery™ is **simple** to install, **safe**, very **reliable**, and provides the lowest lifetime energy cost for both new solar customers and retrofit customers. As an installer, you can design the right system size to meet the needs of the homeowner.



## Simpler

- Quick and easy single person installation
- Plug and play installation
- Interconnects with standard household AC wiring

## Safer

- No high voltage DC in system
- Cells safety tested and certified by TÜV Rheinland
- Prismatic cells are highly stable over time

## Greater Reliability

- Lithium iron phosphate (LFP) chemistry for long cycle life
- 10-year warranty
- Modular design promotes redundancy

# Enphase AC Battery

<b>MODEL NUMBER</b>	
Model B280-1200-LL-I-US00-RF0	
<b>ACCESSORIES</b>	<b>DIMENSIONS</b>
Enphase Wall Mount Bracket (BWM-16IN-A)	Size: 487 mm (W) x 311 mm (H) / 19.2 in. (W) x 12.25 in. (H) accommodates 16 in. battery-to-battery spacing Weight: 3.5 kg (7.7 lbs)
<b>OUTPUT DATA (AC)</b>	<b>@240 VAC</b>
Peak output power	280 VA
Rated (continuous) output power	270 VA
Nominal frequency range	57 – 61 Hz
Nominal output current	1.13 A
Extended line to neutral voltage range	211 – 264 VAC
Extended frequency range	57 – 63 Hz
Power factor (adjustable)	1/0.7 leading ... 0.7 lagging
Maximum units per 20 A branch circuit	14 (single phase)
Peak inverter efficiency	97.3%
<b>BATTERY CHEMISTRY</b>	
Capacity	1.2 kWh
Depth of discharge (usable capacity)	>95%
Ambient operating temperature range	-20° C to 45° C (-4° F to 113° F)
Chemistry	Lithium Iron Phosphate (LFP)
Cell safety certifications	TÜV Rheinland, UL
Roundtrip cell efficiency <sup>1</sup>	96%
<b>MECHANICAL DATA</b>	
Dimensions	390 mm (W) x 325 mm (H) x 220 mm (D) / 15.4 in (W) x 12.8 in (H) x 8.7 in (D) (without bracket)
Weight	25 kg (55 lbs)
Installation	Wall mounted in an indoor space using standard AC wiring in conduit or in wall, where allowed.
Enclosure	Indoor – IP20 / NEMA 2
Cooling	Natural convection – No fans
<b>FEATURES AND COMPLIANCE</b>	
Compatibility	Compatible with grid-tied PV systems using the Enphase Envoy-S Metered™ gateway
Communication	Power Line Communication (PLC), TCP/IP through Envoy-S
Services	Maximizing self-consumption of solar, time-of-use bill management, power export limiting <sup>2</sup>
Monitoring	Enlighten Manager and MyEnlighten monitoring options
Compliance	Certification Pending: UL 1741, UL 1973, UL 9540; UN 38.3
<b>LIMITED WARRANTY</b>	
Limited Warranty <sup>3</sup>	>80% capacity, up to 10 years or 7300 cycles

1. At 25° C (77° F).
2. Optional. requires Enphase S-Series Microinverters™ to implement.
3. Whichever occurs first. Restrictions apply.



YOUR ENPHASE ENERGY DISTRIBUTOR  
SOLARIS  
720-474-6050  
www.solaris-shop.com

To learn more about Enphase offerings, visit [enphase.com](http://enphase.com)