

EV230PDRACNG

EVlink Level 2 Cloud Connected Pedestal Dual 7.2kW Non-Gateway Charging Station

Product availability : Stock - Normally stocked in distribution facility



Price* : 8500.00 USD



Main

Range	EVlink
Product or component type	Cloud connected charging station
Device application	Commercial
Type of installation	Outdoor
Offer type	Non-gateway
Mounting mode	Pedestal mount

Complementary

NEMA degree of protection	NEMA 3R
Material	Enclosure : metallic and white Pedestal : metallic and black
[Us] rated supply voltage	208...240 V ACat 60 Hz, single phase
Supply current	30 A
Poles description	2P (control circuit) 2P + N (power circuit)
Nominal output power	7.2 Wat 30 A, 208...240 V
Level or class	Level 2
Output type	Sides of enclosure : 2 black charging cable of 5.5 m and non retractable
Connector type	SAE J1772
Protection type	Ground fault protection with CCID20 (automatic test at the beginning of each charge cycle) Automatic restart after ground fault or main power loss
Access control system	Chargepoint card Contactless credit card RFID authentication card
Services	Commercial service plan (1...3 yr) to be ordered separately and one per unit Service provider plan (1...3 yr) to be ordered separately and one per unit
Ethernet service	Web browser
Display type	Backlit colour LCD

Information displayed	Charging instructions Configuration Usage fees Charging status
Local signalling	Device fault : 2 red indicator light
Communication network type	ZigBee with a range of 45 m, conforming to IEEE 802.15.4
Height	57.44 in (1459 mm)
Width	12.99 in (330 mm)
Depth	7.05 in (179 mm)
Product weight	114.64 lb(US) (52 kg)
Targeted country	USA Canada

Environment

Standards	CSA C22.2 UL 2594
Product certifications	FCC part 15 class A

Ordering and shipping details

Category	21003 - EV CHARGING STATION BUILDING
Discount Schedule	DE10
GTIN	00785901135845
Nbr. of units in pkg.	1
Package weight(Lbs)	175
Returnability	Y
Country of origin	US