Product data sheet Characteristics

EV230WSR

EVlink Level 2 Wall-Mounted 7.2kW Exterior Charging Station

Product availability: Stock - Normally stocked in distribution facility



Price*: 1800.00 USD



Main

Range	EVlink	
Product or component type	Charging station	
Device application	Residential Commercial	**************************************
Type of installation	Indoor/Outdoor	<u>.</u>
Mounting mode	Wall mount	, i

Complementary

NEMA degree of protection	NEMA 3R
Material	Enclosure : metallic and white
[Us] rated supply voltage	208240 V ACat 60 Hz, single phase
Supply current	30 A
Poles description	2P (power circuit)
Nominal output power	7.2 Wat 30 A, 208240 V
Level or class	Level 2
Output type	Bottom of enclosure : 1 black charging cable of 5.5 m and non retractable
Connector type	SAE J1772
Protection type	Ground fault protection with CCID20 (automatic test at the beginning of each charge cycle) Automatic restart after ground fault or main power loss
Local signalling	Device fault : 1 red indicator light Charge : 1 blue indicator light by blinking Power ON : 1 green indicator light
Height	521 mm
Width	13.11 in (333 mm)
Depth	7.13 in (181 mm)
Product weight	37.48 lb(US) (17 kg)

Environment

Ambient air temperature for operation	-22131 °F (-3055 °C)
Electromagnetic compatibility	Electrostatic discharge: 15 kV open air Electrostatic discharge: 8 kV contact Surge immunity test: 6 kV Immunity to radiated fields: 20 V/m Immunity to conducted disturbances: 20 V Electrical fast transient/burst immunity test: 2 kV
Standards	CSA C22.2 UL 2594
Product certifications	FCC part 15 class B

Ordering and shipping details

<u> </u>	
Category	21003 - EV CHARGING STATION BUILDING
Discount Schedule	DE10
GTIN	00785901695387
Nbr. of units in pkg.	1
Package weight(Lbs)	39
Returnability	Υ
Country of origin	US

Contractual warranty

Warranty period	18 months	