

# Enphase Encharge 3

The **Enphase Encharge 3™** battery is **reliable, smart, simple, and safe**. It provides the lowest lifetime energy costs with backup capability for both new and retrofit solar customers. As an installer, you can quickly design the right system size to meet the needs of the homeowner.



## Reliable

- Proven high-reliability IQ Series Microinverters
- Ten-year limited warranty
- Extensive testing
- Passive cooling (no moving parts/fans)

## Smart

- Utility TOU optimization
- Self consumption
- Remote upgrade
- Mobile app-based monitoring
- Grid-forming capability for backup operation

## Simple

- Fully integrated AC battery system
- Quick and easy plug-and-play installation
- Interconnects with standard household AC wiring

## Safe

- Battery safety tested
- Lithium iron phosphate (LFP) chemistry for maximum safety and longevity

# Enphase Encharge 3

<b>MODEL NUMBER</b>	
ENCHARGE-3-1P-NA	Encharge 3 battery storage system with integrated Enphase Microinverters and BMU. Includes: - One Encharge 3.36kWh base unit (B03-A01-US00-1-3) - One Encharge 3 cover and mounting bracket (B03-C-0350-0)
<b>OUTPUT (AC)</b>	
	<b>@240 VAC<sup>1</sup></b>
Rated (continuous) output power	1.28 kVA
Peak output power	1.92 kVA (10 seconds)
Nominal voltage / range	240/211–264 VAC
Nominal frequency / range	60/57–63 Hz
Rated output current	5.3 A
Power factor (adjustable)	0.85 leading ... 0.85 lagging
Maximum units per 20 A branch circuit	Three units (single phase)
Interconnection	Single phase
Round trip efficiency <sup>2</sup>	89%
<b>BATTERY</b>	
Usable capacity	3.36 kWh
Round trip efficiency	96%
Maximum DC voltage	73.5 V
Ambient operating temperature range	-15° C to 55° C (5° F to 131° F) non-condensing
Optimum operating temperature range	0° C to 30° C (32° F to 86° F)
Chemistry	Lithium iron phosphate (LFP)
<b>MECHANICAL DATA</b>	
Dimensions (WxHxD)	367 mm x 664 mm x 319mm (14.45 in x 26.14 in x 12.56 in)
Weight	One each 44.2 kg (97.4 lbs) base unit plus 8.4 kg (18.6 lbs) cover and mounting bracket; total 52.6 kg (116 lbs)
Enclosure	Outdoor – NEMA 3R
Cooling	Natural convection – No fans
Altitude	Up to 2500 meters (8200 feet)
Mounting	Wall mount
<b>FEATURES AND COMPLIANCE</b>	
Compatibility	Compatible with grid-tied PV systems. Compatible with Enphase IQ Series Micros, Enphase Enpower, and Enphase IQ Envoy for backup operation.
Communication	Wireless 2.4 GHz and 915 MHz
Services	Backup, self-consumption, TOU, Demand Charge, NEM Integrity
Monitoring	Enlighten Manager and MyEnlighten monitoring options; API integration
Compliance	This product will comply with all the required regulatory certifications in the North American markets before launch. Details will be provided in the final data sheet.
<b>LIMITED WARRANTY</b>	
Limited Warranty <sup>3</sup>	>70% capacity, up to 10 years or 4000 cycles

1. Supported in backup/off-grid operation.
2. AC to battery to AC
3. Whichever occurs first. Restrictions apply.

To learn more about Enphase offerings, visit [enphase.com](https://enphase.com)