

FLUSH MOUNT RAIL KIT TWO 93-INCH RAILS


2 Rail Add-On Kit for up to 2 Additional Modules


Save Time and Money

Attractive black rail mounting system provides easy installation, simple wire management, and great strength all in a single box



- Kit contains parts required to mount 2 additional modules when using our 4- or 8- Rail Kits
- Use with modules up to 46-inches wide in portrait orientation
- UPS shippable





One Wrench Size - Install with ease and minimal tools. A 1/2-inch socket fits all fasteners.

UL 2703 Listed - All components meet UL standards and have Class A Fire Rating for Type 1 and 2 modules.

PE Certified - Pre-stamped engineering letters available for most states.

Tamarack Flush Mount 84-inch Rail Kit **Install Two Additional PV Modules***



Black Coated Rails

Attractive low-profile mounting of up to two modules with fourfoot roof attachment spacing. Certified for up to 180 MPH wind speed and 120 PSF snow load. 2 rails included. Two rail heights available - 1.6-inch or 2.3-inch.



Push-In Bonding Rail Splice Quickly splice and bond rail sections with no tools or fasteners. Top Clamps and Rail Mounts can be co-located with splice. 2 splices included.



5050 Clamp

One clamp can be used as a mid-clamp or an end-clamp on modules with 30 mm to 40 mm frame height.

4 clamps included.



Rail Mount and L-Foot

Quickly and securely mount the rail from either side, to Tamarack composition shingle flashings, S-5! metal roof clamps or any roof attachment that can be used with a 5/16 inch bolt. 4 mounts and L-feet included.



Wire Management Clip Clips can be pushed into top of rail to keep cables in place. 6 clips included.

MLPE Adapter

Use this adapter for mounting microinverters and optimizers on the rails under the modules. Use one adapter for each device. 2 adapters included.

