

# MeterHub™

## SOLAR CONTROLLER COMMUNICATIONS HUB



Morningstar's **MeterHub** (HUB-1) allows multiple Morningstar products to communicate over a Meterbus network to provide improved data monitoring, additional capabilities and lower system cost.

- Enables multiple controllers to share a single TriStar meter and display both single controller data (TriStar #1, TriStar #2...) as well as aggregated data for the entire system.
- Enables multiple controllers to share a single Relay Driver and fully utilize all 4 channels of the Relay Driver for different functions (alarms, load disconnects, generator starts) from multiple products.

The MeterHub allows up to 15 Morningstar products on a single MeterBus network. The product electrically isolates devices that supply power to the network, preventing damage to the network in the event of grounding problems. Five status LED's

indicate the proper network connection to each port. The MeterHub is suitable for either wall or DIN rail mounting.


## **KEY FEATURES AND BENEFITS**

#### **Compatible With:**

- SunSaver-MPPT<sup>™</sup>
  - TriStar<sup>™</sup>
  - TriStar-MPPT™
  - TriStar Meter-2<sup>™</sup>
  - TriStar Remote Meter-2<sup>™</sup>
  - Relay Driver™

## Included in the Box:

- MeterHub
- Operator's Manual
- Five Meterbus RJ-11 cables each 1 meter in length
- Four mounting screws



Meter

TriStar

101

## **Typical Network Configuration**

## **TECHNICAL SPECIFICATIONS**

#### Electrical

Minimum Isolation (Ports 1-4)500 VoltsSelf-consumption (per port)8 mA

#### Environmental

Ambient Temperature Storage Temperature Humidity Tropicalization -40°C to +60°C -55°C to +85°C 100% non-condensing Conformal coating-printed circuit board

#### Mechanical

Dimensions

Weight Port Connections Enclosure Compatible DIN rail 13.5 x 10.8 x 3.7 cm 5.3 x 4.3 x 1.5 inch 0.19 kg / 0.41 lbs. RJ-11, gold plated Type 1 (indoor and vented) 35 mm standard

#### Certifications

CE Compliant ETL Recognized (UL1741) RoHS Compliant Manufactured in a certified ISO 9001 facility

WARRANTY: Five year warranty period. Contact Morningstar or your authorized distributor for complete terms.

AUTHORIZED MORNINGSTAR DISTRIBUTOR:



YOUR U \ kV@/8cu<sup>\*</sup> k DISTRIBUTOR SOLIGENT 800-967-6917 www.soligent.net



8 Pheasant Run Newtown, PA 18940 USA Tel. +1-215-321-4457 Fax: +1-215-321-4458 E-mail: <u>info@morningstarcorp.com</u> Website: <u>www.morningstarcorp</u>.

©2009 Morningstar Corporation Printed in USA 223E-Rev 2-9/09