



ITEM NO.	DESCRIPTION	QTY.
1	CAP SCREW, HEX HEAD, 5/16"-18 X 3/4" UNC-2A, GRADE 8	1
2	BASE PLATE, SPECIALTY FLAT TILE	1
3	LAG SCREW, HEX HEAD, 1/4" x 1-1/2", ZINC	4
4	SUB FLASHING, SPECIALTY FLAT TILE, 9.5" X 10" X .032", 3003, MILL	1
5	FLASHING, SPECIALTY FLAT TILE, .032" THICK, 3003 AL, MILL	1
6	COLLAR, COUNTER FLASHING, 1-1/4" ID EPDM	1
7	POST, 1.25" OD X 5.5", 6063-T5, MILL	1
8	WASHER, SEALING, 5/16" ID X 1-1/4" OD, EPDM BONDED SS	1
9	WASHER, FENDER, 5/16" ID X 1" OD, 18-8 SS	1
10	WASHER, SPLIT-LOCK, 5/16" ID, 18-8 SS	1
11	CAP SCREW, HEX HEAD, 5/16"-18 X 1", UNC-2A - 18-8 SS	1

POST & TOP FLASHING AVAILABLE IN MILL, CLEAR ANODIZED, AND BRONZE ANODIZED FINISHES.

Quick Mount PV[®]

TITLE:

QMFTM: SPECIALTY FLAT TILE MOUNT

UNLESS OTHERWISE SPECIFIED:
 DIMENSIONS ARE IN INCHES
 TOLERANCES:
 FRACTIONAL ± 1/16
 TWO PLACE DECIMAL ±.02
 THREE PLACE DECIMAL ±.005

SIZE A	DRAWN BY: MPW	REV 2
	DATE: 7/18/2012	
SCALE: 1:8	WEIGHT: 2.273	SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF QUICK MOUNT PV. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF QUICK MOUNT PV IS PROHIBITED.

DO NOT SCALE DRAWING