

SECURE THE POWERMOUNT BY SCREWING THE SELF-TAPPING STAINLESS STEEL FASTENERS (INCLUDED) INTO/THROUGH THE PRE-PUNCHED HOLES, INTO/THROUGH THE EPDM GASKET, INTO/THROUGH THE ROOF PANEL, AND INTO/THROUGH THE ROOF DECK (IF APPLICABLE). MAKE SURE TO NOT OVER-TIGHTEN AS YOU RISK STRIPPING THE FASTENER. IF A FASTENER IS STRIPPED, REMOVE AND REPLACE WITH A SIMILAR FASTENER, BUT OF A LARGER DIAMETER.

ONCE THE POWERMOUNT IS COMPLETELY FASTENED DOWN, IT IS RECOMMENDED TO CAULK THE ENTIRE PERIMETER WITH AN EQUAL TO OR BETTER THAN TITEBOND SEALANTS FOR METAL, ALUMINUM, STEEL AND GALVANIZED SURFACES.

NOTE: IF THE POWERMOUNT IS INSTALLED ON NON-SMOOTH SURFACE, THE ENTIRE PERIMETER AROUND THE POWERMOUNT MUST BE CAULKED TO ENSURE A PROPER


POWERMOUNT-9000S - SOLARMOUNT INSTALLATION GUIDE




1411 BROADWAY BLVD. NE - ALBUQUERQUE, NM 87102


PHONE: 505.242.6411 WEBSITE: UNIRAC.COM

DRAWN BY:	RJH
DATE:	02/8/18
SCALE:	N.T.S.





POWERMOUNTS IN THE SERIES.



POWERMOUNT-9000S - SOLARMOUNT INSTALLATION GUIDE



2

02/8/18

N.T.S.

DRAWN BY:

DATE: SCALE: