



Main

Range of product	Conext SW
Device short name	SW 2524
Product or component type	Inverter/Charger

Complementary

Type of signal	True sine wave (invert mode)
Continuous power	2400 W for output (invert mode) 2700 W overload for output (invert mode) , duration: 30 min 4000 W surge for output (invert mode) , duration: 5 s
Peak output current	24.3 A for short circuit
Network frequency	50/60 Hz for output (selectable)
Output voltage	12...32 V DC (charge mode) 24 V DC (charge mode) for nominal mode 240 V AC (invert mode) 120 V AC (invert mode)
Output current	65 A (charge mode)
Input voltage	20...34 V DC (invert mode) 135...270 V AC (charge mode) 95...135 V AC (charge mode) 240 V AC (charge mode) 120 V AC (charge mode)
Input current	9 A (charge mode)
Efficiency	90 % (charge mode) 91.5 % (invert mode)
Cos phi	> 0.98 for input
Power consumption in W	< 8 W for search mode
Battery type	FLA Gel AGM
Relay type	Automatic transfert relay at 30 A
Transfer time	<= 16.7 ms
Provided equipment	Battery temperature sensor included for temperature compensation
Height	418 mm
Width	341 mm
Depth	197 mm
Product weight	22.3 kg

Environment

Ambient air temperature for operation	-20...60 °C
Ambient air temperature for storage	-40...85 °C
Standards	UL 1741 CSA C22.2 No 107.1
Product certifications	CSA